



Find your fire.



MECHANICAL
HEATING, COOLING &
PROPERTY MANAGEMENT

2023 Models

Published August 23, 2023



Find your fire.

enerzone

CONTENTS

Small Wood Stoves
 SOLUTION 1.4 WOOD STOVE 4

Medium Wood Stoves
 SOLUTION 1.7 WOOD STOVE..... 5

Large Wood Stoves
 HARMONY 2.3 WOOD STOVE 6
 SOLUTION 2.3 WOOD STOVE..... 7

Extra Large Wood Stoves
 SOLUTION 3.3 WOOD STOVE..... 8
 SOLUTION 3.5 WOOD STOVE..... 9

Small Wood Inserts
 DESTINATION 1.9 WOOD INSERT 10

Medium Wood Inserts
 SOLUTION 1.7-I WOOD INSERT11

Large Wood Inserts
 DESTINATION 2.3 WOOD INSERT12

Large Wood Inserts
 DESTINATION 2.7 WOOD INSERT13
 SOLUTION 2.3 WOOD INSERT14
 SOLUTION 3.5 WOOD INSERT15

Large Wood Fireplace
 SOLUTION 2.5 ZC II WOOD FIREPLACE16

Pellet Stoves
 EUROMAX PELLETT HEATER.....17

Compatible DuraVent products begin on page 19



Find your fire.

Shipping Policy

All shipments leave our warehouse in excellent condition. Our shipping team takes great pride to make sure all orders are packaged to ensure the product arrives in the same condition as it leaves our location. We purchase specific skid sizes to accommodate the products we ship. Any damages or internal damages that occur are done once they leave our building.

We have changed to BLACK SHRINK WRAP, if you receive an order with clear wrap contact your rep or our inside team immediately.

All shipments must be inspected upon receipt. Any signs of damaged must be noted on the bill of lading. If the shipment shows immediate signs of damage you have the following options:

- Refuse the shipment and notify us immediately
- Note on bill of lading “shipment received damage”
- Take photos of the shipment

A crease in any of the packaging could be a sign of internal damage and should be inspected immediately or noted on the bill of lading “subject to inspection” so it can be inspected later. Inspection must be completed within 24 hours of receipt.

Any shipment signed “received in good condition”

National Energy Equipment Inc is not accountable for any damages. We have no recourse with the transportation company. It will be your responsibility to reconcile with the carrier. Freight damages are not eligible for warranty.

Internal Damages:

You have 48 hours to submit a claim for Internal Damages. Photos of the unit and packaging will be required

Return Policy

All returns must have an RMA#. Items returned without an RMA, will be refused. Please contact Hearth Inside Sales for the RMA#. This RMA# must accompany the product. Returned product must be in original packaging and unopened. Multiple photos will be required for all product returns. All product returned will be shipped freight prepaid. Any product received damaged will be returned. Restocking fees are applicable to all returns. Minimum restocking is 25%

Warranty Policy

A warranty form must be completed and emailed to Hearth Inside Sales. Warranty forms are available on our website: www.neefireplaces.ca.

- All forms are in excel format and must be completed in excel format
- On many claims photos will be required
- All replacement warranty parts will be invoiced as a regular order and shipped on your next order or freight collect

Once your warranty claim has been is approved, you will be contacted by Hearth Inside Sales. The item will field scrapped or must be returned.

If the product needs to be returned, an RMA# will be provided to you, and must accompany the part. The part must be returned freight collect.

Find your fire.



SOLUTION 1.4 WOOD STOVE

Enjoy cold days with the unmatched warmth offered by the Solution 1.4 wood stove. Smallest model in the series, its reduced size makes it a versatile appliance with a charming look. Functional and practical, it has a north-south firebox, to load logs over depth, and a sturdy ash lip. The Solution 1.4 is also equipped with side panels with delicate engraved grooves, an arched cast iron door and steel legs. Invite tranquility, comfort, and simplicity in your home.

- Recommended heating area: 250 to 1,200 sq. ft.
- Maximum heat output (dry cordwood): 45,000 BTU/h
- Combustion technology: Non-catalytic
- Smallest model in the series

SBI EB00061

Options & Accessories

PART NUMBER	DESCRIPTION
SBI AC01349	5"Ø fresh air intake register with airtight damper.
SBI AC01420	Rigid firescreen.
SBI AC01421	5"Ø fresh air intake kit for wood stove on legs.
SBI AC02023	Blower with thermodisc.
SBI AC02090	5"Ø x 4' insulated flex pipe for fresh air intake.

Find your fire.



SOLUTION 1.7 WOOD STOVE

Combine refinement and performance at all times, for personalized use and an ever-more accessible heating experience with the all-new Solution 1.7. This fully redesigned model will seduce you with its low ecological footprint at only 1.26 g/h, a rating well below EPA's requirements. Medium-sized, the unit features sleek, elegant lines: side panels with delicate engraved grooves, an arched cast iron door, a slightly curved top, a sturdy ash pan, and a customizable base with six choices of legs or a pedestal. Give meaning to your interior, give yourself the cozy nest you dream of!

- Recommended heating area: 500 to 1,800 sq. ft.
- Maximum heat output (dry cordwood): 65,000 BTU/h
- Combustion technology: Non-catalytic
- Included: Ash drawer with safety lid

SBI EB00055 |

Required Accessories

PART NUMBER	DESCRIPTION
SBI AC01181	Pedestal with ash drawer.
SBI AC01182	Black cast iron traditional legs with ash drawer.
SBI AC01183	Brushed nickel cast iron traditional legs with ash drawer.
SBI AC01184	Black cast iron straight legs with ash drawer.
SBI AC01185	Brushed nickel cast iron straight legs with ash drawer.
SBI AC01186	Black cast iron round legs with ash drawer.
SBI AC01187	Brushed nickel cast iron round legs with ash drawer.

Optional Accessories

PART NUMBER	DESCRIPTION	PRICE
SBI AC01000	130 CFM blower with variable speed control (thermodisc included).	
SBI AC01289	Airmate.	
SBI AC01291	5"ø fresh air intake kit for wood stove on legs.	
SBI AC01299	Rigid firescreen.	
SBI AC01336	5"ø fresh air intake kit for wood stove on pedestal.	

Find your fire.



HARMONY 2.3 WOOD STOVE

The Harmony leaves no one indifferent with its look reminiscent of cast iron appliances, while offering the many advantages of wood stoves made of steel. The detail of the unique Fluted Roman Doric columns provides great elegance. Largely meeting EPA requirements with emissions below 1.54 g/h, the Harmony is an eco-friendly appliance that easily complies with the most stringent North American requirements. Available with a refined black or silver door trim, this unit becomes a serious choice to consider. Installation in a mobile home is allowed and you can add an air supply to the combustion to meet the requirements of domestic energy sources. Its 2.4 cu. ft. combustion chamber makes the Harmony a generous source of heat for your home that will certainly meet your highest expectations.

- Recommended heating area: 500 to 2,100 sq. ft
- Maximum heat output (dry cordwood): 75,000 BTU/h
- Combustion technology: Non-catalytic
- Included: Ash drawer with safety lid

SBI EB00045 |

Required Accessories

PART NUMBER	DESCRIPTION	PRICE
SBI AC01232	Black steel door overlay.	
SBI AC01233	Brushed nickel steel door overlay.	

Optional Accessories

PART NUMBER	DESCRIPTION	PRICE
SBI AC01000	130 CFM blower with variable speed control (thermodisc included).	
SBI AC01236	Moulded refractory panels.	
SBI AC01316	5"Ø fresh air intake kit for wood stove on legs.	
SBI AC01349	5"Ø fresh air intake register with airtight damper.	
SBI AC02090	5"Ø x 4' insulated flex pipe for fresh air intake.	

Find your fire.



SOLUTION 2.3 WOOD STOVE

Once again, Enerzone designs and manufactures a superior quality heater to provide you with the independence and security you and your family are looking for. This brand new large ecological model will be soothing to the soul, especially in times of power failure, during cold seasons. The Solution 2.3 is equipped with side panels fitted with delicate engraved grooves and an arched cast iron door which beautifully highlights the flames. Choose from our pedestal or three leg models, black or brushed nickel, traditional, round or straight. You can also upgrade your appliance with a blower with thermodisc and a rigid firescreen for more comfort.

- Recommended heating area: 1 000 to 2,700 sq. ft.
- Maximum heat output (dry cordwood): 110,000 BTU/h
- Combustion technology: Non-catalytic
- Included: Ash drawer with safety lid and 130 CFM blower with variable speed control and thermodisc

SBI EB00063

Required Accessories

PART NUMBER	DESCRIPTION
SBI AC01124	Pedestal with ash drawer.
SBI AC01206	Black cast iron traditional legs with ash drawer.
SBI AC01208	Brushed nickel cast iron traditional legs with ash drawer.
SBI AC01293	Black cast iron flared legs with ash drawer.
SBI AC01294	Brushed nickel cast iron flared legs with ash drawer.
SBI AC01295	Black cast iron round legs with ash drawer.
SBI AC01296	Brushed nickel cast iron round legs with ash drawer.

Optional Accessories

PART NUMBER	DESCRIPTION
SBI AC01000	130 CFM blower with variable speed control (thermodisc included).
SBI AC01197	Airmate.
SBI AC01211	5"Ø fresh air intake kit for wood stove on legs.
SBI AC01315	Rigid firescreen.
SBI AC01336	5"Ø fresh air intake kit for wood stove on pedestal.
SBI AC01349	5"Ø fresh air intake register with airtight damper.
SBI AC02090	5"Ø x 4' insulated flex pipe for fresh air intake.

Find your fire.



SOLUTION 3.3 WOOD STOVE

Once again, Enerzone designs and manufactures a superior quality heater to provide you with the independence and security you and your family are looking for. This brand new large ecological model will be soothing to the soul, especially in times of power failure, during cold seasons.

The Solution 3.3 is equipped with side panels fitted with delicate engraved grooves and an arched cast iron door which beautifully highlights the flames. Choose from our pedestal or three leg models, black or brushed nickel, traditional, round or straight. You can also upgrade your appliance with a blower with thermodisc and a rigid firescreen for more comfort.

- Recommended heating area: 900 to 2,300 sq. ft.
- Maximum heat output (dry cordwood): 90,000 BTU/h
- Combustion technology: Non-catalytic
- Included: Ash drawer with safety lid

SBI EB00060 |

Required Accessories

PART NUMBER	DESCRIPTION
SBI AC01249	Brushed nickel cast iron traditional legs with ash drawer.
SBI AC01251	Black cast iron traditional legs with ash drawer.
SBI AC01253	Brushed nickel cast iron round legs with ash drawer.
SBI AC01261	Brushed nickel cast iron straight legs with ash drawer.
SBI AC01265	Black cast iron round legs with ash drawer.
SBI AC01267	Black cast iron straight legs with ash drawer.
SBI AC01271	Pedestal with ash drawer.

Optional Accessories

PART NUMBER	DESCRIPTION
SBI AC01000	130 CFM blower with variable speed control (thermodisc included).
SBI AC01336	5"Ø fresh air intake kit for wood stove on pedestal.
SBI AC01349	5"Ø fresh air intake register with airtight damper.
SBI AC01397	Rigid firescreen.
SBI AC01401	Airmate.
SBI AC02090	5"Ø x 4' insulated flex pipe for fresh air intake.

Find your fire.



SOLUTION 3.5 WOOD STOVE

When the winter season sets in, it also brings “cooing” rituals. Designed to replace your old ineffective masonry fireplace, the Solution 3.5 is your best choice for creating the perfect ambiance. Comfort, performance, pleasure, economy and saving are at the core of your heating experience with this wood insert designed for large spaces, in addition to being very respectful of the environment. Thanks to its new ultra-efficient and clean secondary combustion system, this non-catalytic appliance offers a dazzling spectacle as the flames roll between the logs, through the large glass surface. Complete your installation with the faceplate and trims of your choice. A firescreen is also available for those who wish to fully experience the crackle of a good wood fire.

- Recommended heating area: 1 000 to 2,700 sq. ft.
- Maximum heat output (dry cordwood): 110,000 BTU/h
- Combustion technology: Non-catalytic
- Included: Ash drawer with safety lid and 130 CFM blower with variable speed control and thermodisc

SBI EB00053 |

Optional Accessories

PART NUMBER	DESCRIPTION
SBI AC01234	Airmate.
SBI AC01281	Rigid firescreen.
SBI AC01336	5”ø fresh air intake kit for wood stove on pedestal.

Extra Large Wood Stoves

Find your fire.



DESTINATION 1.9 WOOD INSERT

Designed for the smallest masonry hearths thanks to its tapered shape, the Destination 1.9 is a compact and easy to install wood insert. Its non-catalytic combustion and its 82% efficiency rate (the highest in its category) make it the perfect choice for those who want to transform their open fireplace into a clean and efficient heat source. To facilitate use and maintenance, its firebox has a hollow bottom for the accumulation of ashes, which helps reduce the frequency of cleaning. Enjoy a panoramic view of the fire thanks to its large ceramic glass and arched cast iron door, fitted with a discreet black wood handle. The flush mount blower and the removable handle air control concealed in the faceplate louver give the Destination 1.9 a modern, clean finish that showcases the beauty of the flames

- Recommended heating area: 250 to 1,200 sq. ft.
- Maximum heat output (dry cordwood): 45,000 BTU/h
- Combustion technology: Non-catalytic
- Included: 90 CFM blower with variable speed control

SBI EB00066 |

Options & Accessories

PART NUMBER	DESCRIPTION
SBI AC01213	Rigid firescreen.
SBI AC01214	Offset liner adapter.
SBI AC01298	5"Ø fresh air intake kit.
SBI AC01349	5"Ø fresh air intake register with airtight damper.
SBI AC02006	System hook up liner.
SBI AC02082	32" x 44" cuttable faceplate (18 ga).
SBI AC02090	5"Ø x 4' insulated flex pipe for fresh air intake.

Find your fire.



SOLUTION 1.7-I WOOD INSERT

The Enerzone team is once again innovating and living up to its reputation with the completely new Solution 1.7, which achieves incomparable performance of 1.26 g/h. This non-catalytic insert benefits from a state-of-the-art second combustion system. The first-class materials, the arched cast iron door with delicate curves, the positioning of the silver grooves, the high density refractory bricks, the standard silent fan are all assets that make this unit an easy-to-operate insert that has this little extra. It gives its owner unparalleled comfort, increased durability and superior reliability.

A faceplate extension is included with this unit for installation in most hearths

- Recommended heating area: 500 to 1,800 sq. ft.
- Maximum heat output (dry cordwood): 65,000 BTU/h
- Combustion technology: Non-catalytic
- Included: 144 CFM blower with variable speed control

SBI EB00057 |

Required Accessories

PART NUMBER	DESCRIPTION
SBI AC01285	Large faceplate (32" x 50").
SBI AC01287	Regular faceplate (29" x 44").
SBI OA10122	Black faceplate trims (29" x 44").
SBI OA10123	Brushed nickel faceplate trims (29" x 44").
SBI OA10128	Black large faceplate trims (32" x 50").
SBI OA10129	Brushed nickel large faceplate trims (32" x 50").

Optional Parts & Accessories

PART NUMBER	DESCRIPTION	PRICE
SBI AC01214	Offset liner adapter.	
SBI AC01298	5"ø fresh air intake kit.	
SBI AC01299	Rigid firescreen.	
SBI AC01349	5"ø fresh air intake register with airtight damper.	
SBI AC02090	5"ø x 4' insulated flex pipe for fresh air intake.	

Find your fire.



DESTINATION 2.3 WOOD INSERT

The Destination 2.3 is really a blend of technological improvement and design advancement. Cast iron was the material of choice for the smooth contemporary surround and designed for a flush finish designed to be installed in a masonry fireplace. An optional backing plate is available for larger masonry openings. Maintenance of electrical components was made easy with the conception of a slick, drawer-like system to which the blower assembly attaches. The heat activated blower assembly (90 CFM) can be operated in automatic, manual or OFF mode. Maintenance of electrical components was made easy with the conception of a slick, drawer-like system to which the blower assembly attaches. The blower assembly (90 CFM) is equipped with a heat sensor and a switch that can be set to automatic, manual or OFF position

- Recommended heating area: 500 to 2,100 sq. ft.
- Maximum heat output (dry cordwood): 75,000 BTU/h
- Combustion technology: Non-catalytic
- Included: 90 CFM blower with variable speed control

SBI EB00044 |

Optional Accessories

PART NUMBER	DESCRIPTION	PRICE
SBI AC01214	Offset liner adapter.	
SBI AC01298	5"Ø fresh air intake kit.	
SBI AC01315	Rigid firescreen.	
SBI AC01321	Bottom faceplate backing plate 44" x 6".	
SBI AC01322	29" x 44" faceplate backing plate kit.	
SBI AC01323	2" or 4" projection kit for insert.	
SBI AC01332	29" x 50" faceplate backing plate kit.	
SBI AC01333	Bottom faceplate backing plate 50" x 6".	
SBI AC01349	5"Ø fresh air intake register with airtight damper.	
SBI AC02090	5"Ø x 4' insulated flex pipe for fresh air intake.	

Find your fire.



DESTINATION 2.7 WOOD INSERT

Enerzone invites you to a new experience in wood burning insert. Our design experts have created the best in uncompromising aesthetics and functionality. The Destination 2.7 stands out at first sight with its eloquent cast iron faceplate adorned with a distinctive louver and its large glass surface for an assertive, and distinguished style. Despite its large size, this tapered insert offers a very large viewing area, yet fits into many size restrictive masonry fireplaces. A cuttable faceplate, a fresh air intake and a fire screen door are available for further customization. Equipped with incomparable performance, this insert offers 80,000 BTU/h with an emission rate of only 1.14 g/h; a value well below the next EPA standards. Require nothing less than an Enerzone appliance to enjoy precious moments of relaxation in the comfort of your home!

- Recommended heating area: 750 to 2,200 sq. ft.
- Maximum heat output (dry cordwood): 80,000 BTU
- Combustion technology: Non-catalytic
- Included: 176 CFM blower with variable speed control

SBI EB00058 |

Optional Accessories

PART NUMBER	DESCRIPTION
SBI AC01214	Offset liner adapter.
SBI AC01263	2" or 4" projection kit for insert.
SBI AC01275	Firescreen door.
SBI AC01277	34" x 50" cuttable faceplate (18 ga).
SBI AC02006	System hook up liner.
SBI AC01298	5"Ø fresh air intake kit.

Find your fire.



SOLUTION 2.3 WOOD INSERT

Designed to be a powerful unit, the Solution 2.3 insert offers a surprising quality of combustion. Every detail is thoughtfully planned to optimize its performance, which far exceeds the latest industry standards. Many of its features are identical to its freestanding counterpart. Strategically positioned, a powerful heat-activated fan (144 CFM) allows an optimal redistribution of the heat produced by the firebox in the room. In addition, its design allows it to receive a faceplate whose dimensions can cover a masonry hearth with a maximum height of 32 inches and width of 50 inches. Designed for those looking for an eco-friendly and efficient stove; the best of both worlds!

- Recommended heating area: 500 to 2,100 sq. ft
- Maximum heat output (dry cordwood): 75,000 BTU/h
- Combustion technology: Non-catalytic
- Included: 144 CFM blower with variable speed control

SBI EB00064 |

Required Accessories

PART NUMBER	DESCRIPTION	PRICE
B		
SBI AC01290	Regular faceplate (29" x 44").	
SBI AC01292	Large faceplate (32" x 50").	
C		
SBI OA10122	Black faceplate trims (29" x 44").	
SBI OA10123	Brushed nickel faceplate trims (29" x 44").	
SBI OA10128	Black large faceplate trims (32" x 50").	
SBI OA10129	Brushed nickel large faceplate trims (32" x 50").	

Optional Accessories

PART NUMBER	DESCRIPTION	PRICE
SBI AC01214	Offset liner adapter.	
SBI AC01298	5"Ø fresh air intake kit.	
SBI AC01315	Rigid firescreen.	
SBI AC01317	7 3/16" x 26" heat shield for surround/shelf.	
SBI AC01349	5"Ø fresh air intake register with airtight damper.	
SBI AC01357	32" x 50" cuttable faceplate (18 ga).	
SBI AC02090	5"Ø x 4' insulated flex pipe for fresh air intake.	

Requires the addition of accessories (B) and (C) to complete the unit

Find your fire.



SOLUTION 3.5 WOOD INSERT

When the winter season sets in, it also brings “cooing” rituals. Designed to replace your old ineffective masonry fireplace, the Solution 3.5 is your best choice for creating the perfect ambiance. Comfort, performance, pleasure, economy and saving are at the core of your heating experience with this wood insert designed for large spaces, in addition to being very respectful of the environment.

Thanks to its new ultra-efficient and clean secondary combustion system, this non-catalytic appliance offers a dazzling spectacle as the flames roll between the logs, through the large glass surface. Complete your installation with the faceplate and trims of your choice. A firescreen is also available for those who wish to fully experience the crackle of a good wood fire.

- Recommended heating area: 1,000 to 2,700 sq. ft.
- Maximum heat output (dry cordwood): 110,000 BTU/h
- Combustion technology: Non-catalytic
- Blower not required

SBI EB00062 |

Required Accessories

PART NUMBER	DESCRIPTION
B	
SBI AC01229	Regular faceplate (32" x 44").
SBI AC01273	Large faceplate (32" x 50").
C	
SBI OA10125	Black faceplate trims (32" x 44").
SBI OA10126	Brushed nickel faceplate trims (32" x 44").
SBI OA10128	Black large faceplate trims (32" x 50").
SBI OA10129	Brushed nickel large faceplate trims (32" x 50").

Optional Accessories

PART NUMBER	DESCRIPTION
SBI AC01214	Offset liner adapter.
SBI AC01281	Rigid firescreen.
SBI AC01298	5"ø fresh air intake kit.

Find your fire.



SOLUTION 2.5 ZC II WOOD FIREPLACE

The fireplace has always been the heart of the living room. A unifying element, to this day it is still one of the most coveted projects of previous generations as well as those to come.

Designed to fulfill your expectations, the Solution 2.5 ZC II clearly stands out from other fireplaces. Endowed with exceptional performance and efficiency that is far ahead of the competition. With the consumer for whom wood is a clean and renewable source of heating in mind, Enerzone designers created this non-catalytic unit that truly stands out. Experience wood heating in its most complete form.

- Recommended heating area: 750 to 2,200 sq. ft.
- Maximum heat output (dry cordwood): 80,000 BTU/h
- Combustion technology: Non-catalytic
- Included: 176 CFM blower with variable speed control

SBI EB00059 |

Required Accessories

PART NUMBER	DESCRIPTION
SBI AC01255	Black faceplate.
SBI AC01256	Traditional style louvers.
SBI AC01257	Rustic style louvers.

Optional Accessories

PART NUMBER	DESCRIPTION
SBI AC01223	Heat shield for surround/shelf.
SBI AC01275	Firescreen door.
SBI AC01347	4"Ø fresh air intake register with airtight damper.
SBI AC01350	6"Ø x 25' insulated flex pipe for forced air kit.
SBI AC01374	Forced air kit.
SBI AC01375	Traditional gravity kit.
SBI AC01389	Modern gravity kit with adjustable pipes.
SBI AC09200	Fireplace carrying handles.

Find your fire.



EUROMAX PELLET HEATER

The Euromax is as close as you can get to a pellet furnace. It is equipped with a 125-pound hopper. Its state-of-the-art LCD control lets you choose between various settings with the touch of a finger. The bottom feed technology used inside the Euromax minimizes burn pot maintenance while allowing a more complete and efficient combustion.

Affordable, intelligent, stylish and clean...This is heating in the 21st Century.

SBI EPO0070

Required Accessories

PART NUMBER	DESCRIPTION
SBI AC01220	Black cast iron door overlay.
SBI AC01222	Brushed nickel cast iron door overlay.

Optional Accessories

PART NUMBER	DESCRIPTION
SBI AC01240	3"ø x 5' fresh air intake kit.
SBI AC01343	Hot air distribution kit.
SBI AC01460	Storage tank with pneumatic self-feeding pellet system.
SBI AC01462	Storage tank extension for ac01460.
SBI AC01463	Stand alone auxiliary discharge tank.
SBI AC01464	Leg assembly for ac01463 discharge tank.
SBI AC01465	2"ø x 25' anti-static flex hose.
SBI AC02092	3"ø x 10' insulated flex pipe for fresh air intake.
SBI AC02703	Tempered glass hearth pad 10 mm - 54" x 46 3/4".
SBI AC02704	Tempered glass hearth pad 10 mm - 44" x 36".
SBI AC05558	Digital wall thermostat.

duravent™

DuraTech® Canada
High Temperature, 1" Double-Wall,
All-Fuel Chimney System
ULC S629, ULC S604, and UL 103HT



Effective May 1, 2023.
Published May 11, 2023.
Prices subject to change without notice.